


TSL-470

Soap
dispenser

The TSL-470 is a stainless-steel pump-action wall mounted soap dispenser, that utilises a concealed soap replenishment system.



CODES

TSL-470CS
TSL-470CP
TSL-470BK
TSL-470BZ
TSL-470BR

FINISHES

Brushed stainless steel finish
Brushed copper finish
Brushed black finish
Brushed bronze finish
Brushed brass finish

TECHNICAL DATA

Weight	1lb 15oz
Recommended soap viscosity	100 to 3800cPs Liquid soap only. Not for use with foam soap, alcohol gel or hand sanitizer
Body	316AISI stainless steel
Recommended soap system	L-ST series, to be specified separately
Feed pipe connection	8mm push-fit connector to L-ST series feed system
Tested to	2,000,000 depressions
Standard discharge	0.03 fl oz

SPARE PARTS

There are no user-serviceable spare parts



INSTALLATION GUIDELINES

Wall cut out	$\frac{11}{16}$ " diameter
Maximum wall thickness	$\frac{1}{2}$ " - 2"
Reservoir location	Soap reservoir must be mounted below the dispenser. The dispenser is not designed to draw soap from a reservoir mounted above.

RELATED PRODUCTS

TSL-880	Sensor tap
---------	------------

RELATED DOCUMENTS

Installation and maintenance manual	email: technical@thesplashlab.com
Warranty document	email: technical@thesplashlab.com

TECHNICAL DRAWING

