

L-899

Soap Dispenser

Deck mounted sensor operated soap dispenser with straight spout.



Codes

L-899

Technical Data

Finishes	C (Chrome) / CS (Satin)
Warranty	12 months from date of purchase
Weight	1.22Kg (2lb 11oz)
Recommended soap viscosity	100 to 3800 cPs For liquid soap only. Not for use with foam soap, alcohol gel or hand sanitizer.
Soap system (included)	1 litre soap bottle and pump (0.26 GAL (US))
Power supply	Mains power (IP68 rated 12V transformer with push-fit cabling to dispenser)

Spare Parts

L150026	Pump
L150039	Transformer - 12V - to be hard wired
L07100020	Bottle - 1L (0.26 GAL (US))
L150011	Sensor

Optional Accessories

L150038	Pump for multi-feed installation - 1 required per dispenser
L150050	Multi-feed soap reservoir with top fill for sensor soap dispensers
L150051	Sensor operated soap dispenser multi-feed soap reservoir (see separate datasheet for multifeed system)
L07100008	Remote control for soap dispenser



L-899 Soap Dispenser

Installation Requirements

Counter top cutout required (dia)	28mm (1 ⁷ / ₆₄ ")
Maximum countertop thickness	50mm (2")
Access requirements	Pumps and transformers must be accessible at all times for servicing.
Reflective surfaces	Not to be installed opposite a mirror, or other reflective surfaces.
Washroom layout	To prevent sensor malfunction, avoid installing directly opposite other sensor taps/soap dispensers.
Power supply	Must be installed on its own power circuit to avoid interference from other power demands.
Cabling	3 amp fused spur to IP68 rated transformer; low voltage push fit connector to dispenser.
Distance from dispenser to reservoir	Single feed - 900mm Multi feed - 3m

Compliance

cUL
CE

Related Products

Sensor Tap [L-980](#)

Related Documents

Installation manual	email: technical@lovair.com
Operation and maintenance manual	email: technical@lovair.com
Warranty document	email: technical@lovair.com

L-899 Soap Dispenser

Technical Drawing

