

TSL.C.050

CHANNEL FAUCET

A wall-mounted sensor faucet for touchless restrooms, The Channel System Faucet has a pleasingly sleek silhouette that is both durable and delicate and reliable IR sensor in front of the nozzle for an easily triggered water flow.



Codes	Name	Finish
TSL.C.050.CS	Channel System Faucet	Brushed stainless
TSL.C.050.BK	Channel System Faucet	Brushed black
TSL.C.050.BR	Channel System Faucet	Brushed brass
TSL.C.050.CP	Channel System Faucet	Brushed copper
TSL.C.050.C	Channel System Faucet	Bright polished (stainless steel)

Power

Power supply - mains Input 100-240V ac; 50/60Hz | Output 6V DC, 0.5A, 3W max

Input/Output

Comfort delay	2 seconds
Operating pressure	7 - 87 psi dynamic pressure
Flow rate	0.5 GPM (other flow rates available upon request)
Security time	60 seconds
Sensor preset	5"
Sensor range - min.	3" ± 20%
Sensor range - max.	5.9" ± 20%



Composition

Weight	2lb 3oz
Material	AISI316 stainless steel

Related Products

TSL.C.040	Channel soap dispenser
TSL.C.060	Channel hand dryer

Installation Requirements

Placement	Please consult installation manual.
Access	Ensure that mechanism is easily accessible for servicing.

Warranty

1 year parts + labor

Approvals + Compliances

ASME A112.18.1, CSA B125.1, NSF/ANSI/CAN 61,
WRAS, RoHS, ADA

For specifier/architect approval:

Project name		Code (w/ finish)	
Flow rate	<input type="checkbox"/> 0.35 GPM <input type="checkbox"/> 0.5 GPM	Quantity	
Signed		Date	

THE SPLASH LAB

Technical Drawings

